

# 寸法・配筋及び質量表

単位 mm

種類	呼び名	寸法																			重心位置 Y	配筋		参考質量 (kg)				
		B	H	D	D'	h	d	a	a <sub>1</sub>	a <sub>2</sub>	b	c	e	f	g	s	r	c <sub>1</sub>	c <sub>2</sub>	c <sub>3</sub>		i	j		横鉄筋 径 本数	縦鉄筋 径 本数		
歩道用 KDS	300×500	565	675	300	260	500	359	132.5	68.5	60	100	75	130	180	365	75	50	20	50	45	15	30	304	D 6	20	φ 5	11	598
	300×600	565	775	300	252	600	350	132.5	68.5	60	100	75	130	180	465	75	50	20	50	45	15	30	355	D 6	28	φ 5	13	662
	300×700	565	880	300	244	700	352	132.5	68.5	60	100	80	130	180	570	75	50	20	50	50	15	30	402	D10	16	D 6	13	753
	300×800	565	985	300	236	800	355	132.5	68.5	60	100	85	130	180	675	75	50	20	60	55	15	30	448	D10	20	D 6	15	845
	300×900	565	1090	300	228	900	357	132.5	68.5	60	100	90	130	180	780	75	50	30	55	50	15	30	492	D10	22	D 6	15	941
	300×1000	565	1195	300	220	1000	359	132.5	68.5	60	100	95	130	180	885	75	50	30	60	55	15	30	536	D10	26	D 6	17	1,043
	350×500	615	675	350	310	500	409	132.5	68.5	60	100	75	130	180	365	75	50	20	50	45	15	30	297	D 6	20	φ 5	11	615
	350×600	615	775	350	302	600	400	132.5	68.5	60	100	75	130	180	465	75	50	20	50	45	15	30	347	D 6	28	φ 5	13	679
	350×700	615	880	350	294	700	402	132.5	68.5	60	100	80	130	180	570	75	50	20	55	50	15	30	393	D10	16	D 6	13	772
	350×800	615	985	350	286	800	405	132.5	68.5	60	100	85	130	180	675	75	50	20	60	55	15	30	438	D10	20	D 6	15	866
	350×900	615	1090	350	278	900	407	132.5	68.5	60	100	90	130	180	780	75	50	30	55	50	15	30	483	D10	22	D 6	15	963
	350×1000	615	1195	350	270	1000	409	132.5	68.5	60	100	95	130	180	885	75	50	30	60	55	15	30	526	D10	26	D 6	17	1,066
KDS-S (サレントタイプ)	400×600	675	775	400	352	600	448	137.5	68.5	65	100	75	130	180	465	75	70	20	50	45	15	30	343	D 6	28	φ 5	13	726
	400×700	675	880	400	344	700	451	137.5	68.5	65	100	80	130	180	570	75	70	20	55	50	15	30	390	D10	16	D 6	13	821
	400×800	675	985	400	336	800	453	137.5	68.5	65	100	85	130	180	675	75	70	20	60	55	15	30	435	D10	20	D 6	15	919
	400×900	675	1090	400	328	900	456	137.5	68.5	65	100	90	130	180	780	75	70	30	55	50	15	30	479	D10	22	D 6	15	1,020
	400×1000	675	1195	400	320	1000	458	137.5	68.5	65	100	95	130	180	885	75	70	30	60	55	15	30	523	D10	26	D 6	17	1,127
	※500×500	775	695	500	460	500	556	137.5	68.5	65	120	75	150	180	365	75	70	20	50	45	15	30	287	D 6	24	φ 5	12	707
	※500×600	775	800	500	452	600	559	137.5	68.5	65	120	80	150	180	470	75	70	20	55	50	15	30	333	D 6	28	φ 5	14	800
	※500×800	775	1010	500	436	800	565	137.5	68.5	65	120	90	150	180	680	75	70	30	55	50	15	30	422	D10	20	D 6	16	1,004
	※500×1000	775	1220	500	420	1000	569	137.5	68.5	65	120	100	150	180	890	75	70	30	65	60	15	30	507	D10	26	D 6	18	1,222
	※500×1200	775	1435	500	404	1200	584	137.5	68.5	65	120	115	150	180	1105	70	70	40	70	65	15	30	591	D10	28	D 6	20	1,527
車道用 KDR	600×600	875	800	600	552	600	659	137.5	68.5	65	120	80	150	180	470	75	70	20	55	50	15	30	320	D 6	28	φ 5	14	837
	600×800	875	1010	600	536	800	665	137.5	68.5	65	120	90	150	180	680	75	70	30	55	50	15	30	406	D10	20	D 6	16	1,047
	600×1000	875	1220	600	520	1000	669	137.5	68.5	65	120	100	150	180	890	75	70	30	65	60	15	30	491	D10	26	D 6	18	1,270
	600×1200	875	1435	600	504	1200	684	137.5	68.5	65	120	115	150	180	1105	70	70	40	70	65	15	30	573	D10	28	D 6	20	1,582
	300×500	605	740	300	260	500	428	152.5	65.5	80	130	110	170	170	400	60	50	40	65	60	20	35	321	D 6	28	φ 5	11	889
	300×600	605	840	300	252	600	421	152.5	65.5	80	130	110	170	170	500	65	50	40	65	60	20	35	370	D 6	28	φ 5	13	969
	300×700	605	940	300	244	700	412	152.5	65.5	80	130	110	170	170	600	65	50	40	65	60	20	35	420	D10	16	D 6	13	1,066
	300×800	605	1040	300	236	800	402	152.5	65.5	80	130	110	170	170	700	65	50	40	65	60	20	35	470	D10	20	D 6	15	1,160
	300×900	605	1145	300	228	900	405	152.5	65.5	80	130	115	170	170	805	65	50	40	70	65	20	35	517	D10	24	D 6	15	1,283
	300×1000	605	1255	300	220	1000	419	152.5	65.5	80	130	125	170	170	915	65	50	40	80	75	20	35	559	D10	26	D 6	17	1,445
KDR-S (サレントタイプ)	350×500	655	740	350	310	500	478	152.5	68.5	80	130	110	170	170	400	60	50	40	65	60	20	35	314	D 6	28	φ 5	11	914
	350×600	655	840	350	302	600	471	152.5	68.5	80	130	110	170	170	500	65	50	40	65	60	20	35	362	D 6	28	φ 5	13	995
	350×700	655	940	350	294	700	462	152.5	68.5	80	130	110	170	170	600	65	50	40	65	60	20	35	411	D10	16	D 6	13	1,092
	350×800	655	1040	350	286	800	452	152.5	68.5	80	130	110	170	170	700	65	50	40	65	60	20	35	461	D10	20	D 6	15	1,186
	350×900	655	1145	350	278	900	455	152.5	68.5	80	130	115	170	170	805	65	50	40	70	65	20	35	507	D10	24	D 6	15	1,311
	350×1000	655	1255	350	270	1000	469	152.5	68.5	80	130	125	170	170	915	65	50	40	80	75	20	35	550	D10	26	D 6	17	1,475
	400×600	725	840	400	352	600	516	162.5	68.5	90	130	110	170	170	500	65	70	40	65	60	20	35	363	D 6	28	φ 5	13	1,077
	400×700	725	940	400	344	700	507	162.5	68.5	90	130	110	170	170	600	65	70	40	65	60	20	35	413	D10	16	D 6	13	1,179
	400×800	725	1040	400	336	800	499	162.5	68.5	90	130	110	170	170	700	65	70	40	65	60	20	35	462	D10	20	D 6	15	1,278
	400×900	725	1145	400	328	900	502	162.5	68.5	90	130	115	170	170	805	65	70	40	70	65	20	35	509	D10	24	D 6	15	1,409
400×1000	725	1255	400	320	1000	516	162.5	68.5	90	130	125	170	170	915	65	70	40	80	75	20	35	552	D10	26	D 6	17	1,580	

注) 縦鉄筋のD 6は、φ 6を用いてもよい。 ※印 受注生産となります。